

## **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06) Printed in U.S.A.



## **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06) Printed in U.S.A.



### **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06) Printed in U.S.A.

Printed in U.S.A.



## **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06)



## **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06) Printed in U.S.A.



## **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06) Printed in U.S.A.



### **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06) Printed in U.S.A.



# **WARNING:**

Contrary to the current installation procedures recommended by certain gasket suppliers, the gasket in this set **does not** require the use of RTV silicone sealant applied in a 1/4" bead on top of the existing beading on both sides of the gasket.

This gasket has a taller sealing bead on the oil pan side of the gasket to accomodate the uneven (rippled) sealing surfaces of the oil pan.

A small dab of RTV silicone sealant is recommended only at the 4 corner joints on the engine block where rear bearing cap and front cover meet the gasket.

© 2006 Federal-Mogul Corporation Form No. I-2066 (Rev. 10/06)