KENDA

AMERICAN ENGINEERED TRACTION

KANINE

EXTREME TRACTION

The **Kenda Kanine** is engineered to deliver greater mileage than stock tires while providing better handling than passenger car replacements. Its high-performance tread pattern reduces rolling resistance without sacrificing maximum lateral traction for confident cornering and stability. Increased siping evacuates standing water from the contact surface for excellent wet-weather performance. Built to motorcycle-specific standards for the **Can-Am® Spyde**r and BRP Rykers, **and is now available in sizes designed specifically for the Harley Davidson® Trike applications.**

K R 2 0 **S T R E E T**



TIRE SPECIFICATIONS

Kenda USA Part #	FRONT/REAR	SIZE	SPEED/ LOAD RATING	SW(in)	OD(in)	MAX PSI	TREAD DEPTH (mm)	TT/TL
04KR2001	FRONT	145/60R16	66T	6	23	44	7.30	TL
042015001A1	FRONT	165/55R15	69H	7	23	44	6.80	TL
042015002A1	REAR	225/50R15	84H	9	24	44	8.20	TL
04KR2002	REAR	205/55R15	81T	8	24	44	8.60	TL
04KR2004	REAR	205/65R15	92T	8	23	44	7.90	TL
04KR2003	REAR	205/45R16	77T	8	25	44	8.20	TL



