



FEL-PRO INSTALLATION TIPS

IMPORTANT: If the cylinder block deck surface has been machined a thicker head gasket must be installed. For gasket thickness identification purposes, these gaskets have notches on the outer edge and can be identified as follows.

1 notch = standard thickness. Install if cylinder block deck height is 12.7164" +/- .0039"

2 notches = .0098" thicker. Install if cylinder block deck height is 12.7067" +/- .0039".

3 notches = .0197" thicker. Install if cylinder block deck height is 12.6968" +/- .0039".



FEL-PRO INSTALLATION TIPS

IMPORTANT: If the cylinder block deck surface has been machined a thicker head gasket must be installed. For gasket thickness identification purposes, these gaskets have notches on the outer edge and can be identified as follows.

1 notch = standard thickness. Install if cylinder block deck height is 12.7164" +/- .0039"

2 notches = .0098" thicker. Install if cylinder block deck height is 12.7067" +/- .0039".

3 notches = .0197" thicker. Install if cylinder block deck height is 12.6968" +/- .0039".



FEL-PRO INSTALLATION TIPS

IMPORTANT: If the cylinder block deck surface has been machined a thicker head gasket must be installed. For gasket thickness identification purposes, these gaskets have notches on the outer edge and can be identified as follows.

1 notch = standard thickness. Install if cylinder block deck height is 12.7164" +/- .0039"

2 notches = .0098" thicker. Install if cylinder block deck height is 12.7067" +/- .0039".

3 notches = .0197" thicker. Install if cylinder block deck height is 12.6968" +/- .0039".



FEL-PRO INSTALLATION TIPS

IMPORTANT: If the cylinder block deck surface has been machined a thicker head gasket must be installed. For gasket thickness identification purposes, these gaskets have notches on the outer edge and can be identified as follows.

1 notch = standard thickness. Install if cylinder block deck height is 12.7164" +/- .0039"

2 notches = .0098" thicker. Install if cylinder block deck height is 12.7067" +/- .0039".

3 notches = .0197" thicker. Install if cylinder block deck height is 12.6968" +/- .0039".

