

# **FEL-PRO INSTALLATION TIPS**

## PLASTIC COMPOSITE WATER OUT-LET AND WATER PUMP GASKETS

The water outlet and/or water pump gasket(s) contained in this set is a new composite construction resulting from extensive engineering and extreme testing conditions. This new compound gasket offers the following featured.

If mating surface is pitted or corroded apply a aasket sealer to both sides of gasket(s).

PRIOR TO INSTALLATION insert mounting bolts through the casting and the Hole Lock bolt hole locations in the gasket.

ATTACH AND ALIGN ASSEMBLY.

- Continued -



## FEL-PRO INSTALLATION TIPS

## PLASTIC COMPOSITE WATER OUT-LET AND WATER PUMP GASKETS

The water outlet and/or water pump gasket(s) contained in this set is a new composite construction resulting from extensive engineering and extreme testing conditions. This new compound gasket offers the following featured.

If mating surface is pitted or corroded apply a gasket sealer to both sides of gasket(s).

**PRIOR TO INSTALLATION** insert mounting bolts through the casting and the Hole Lock bolt hole locations in the gasket.

ATTACH AND ALIGN ASSEMBLY.

- Continued -



# **FEL-PRO INSTALLATION TIPS**

#### PLASTIC COMPOSITE WATER OUT-LET AND WATER PUMP GASKETS

The water outlet and/or water pump gasket(s) contained in this set is a new composite construction resulting from extensive engineering and extreme testing conditions. This new compound gasket offers the following featured.

If mating surface is pitted or corroded apply a gasket sealer to both sides of gasket(s).

**PRIOR TO INSTALLATION** insert mounting bolts through the casting and the Hole Lock bolt hole locations in the gasket.

ATTACH AND ALIGN ASSEMBLY.

- Continued -

Printed in U.S.A.

Form No. I-3TEMP (Rev. 9/8/00)

© 2000 Federal-Mogul Corporation

Additional sealers are not generally required.

installation. Hole Lock design holds gasket in place during

sesiability Patented sealing bead design provides superior

Withstands high and low temperatures

Printed in U.S.A.

Form No. I-3TEMP (Rev. 9/8/00) © 2000 Federal-Mogul Corporation

Additional sealers are not generally required.

installation. Hoje Fock design holds gasket in place during

sealability Patented sealing bead design provides superior

Withstands high and low temperatures

Printed in U.S.A.

Form No. I-3TEMP (Rev. 9/8/00) © 2000 Federal-Mogul Corporation

Additional sealers are not generally required.

installation. Hoje Fock design holds gasket in place during

sealability Patented sealing bead design provides superior

Withstands high and low temperatures



# **SAIT NOITALLATSNI OR9-133**

LET AND WATER PUMP GASKETS PLASTIC COMPOSITE WATER OUT-

guied in this set is a new composite construction The water outlet and/or water pump gasket(s) con-

ters the following featured. testing conditions. This new compound gasket ofresulting from extensive engineering and extreme

gasket sealer to both sides of gasket(s). If mating surface is pitted or corroded apply a

through the casting and the Hole Lock bolt hole PRIOR TO INSTALLATION insert mounting bolts

ATTACH AND ALIGN ASSEMBLY. locations in the gasket.

- Continued -

sealability

installation.

# **SAIT NOITALLATENI OR9-137**

LET AND WATER PUMP GASKETS PLASTIC COMPOSITE WATER OUT-

fers the following featured. testing conditions. This new compound gasket ofresulting from extensive engineering and extreme rained in this set is a new composite construction Lue water outlet and/or water pump gasket(s) con-

gasket sealer to both sides of gasket(s). If mating surface is pitted or corroded apply a

locations in the gasket. through the casting and the Hole Lock bolt hole etlod gnitruom traeni NOITALLATENI OT ROIRG

- beunifnoo -ATTACH AND ALIGN ASSEMBLY.

Form No. I-3TEMP (Rev. 9/8/00)

Form No. I-3TEMP (Rev. 9/8/00)

Printed in U.S.A.

- beunifnoo -

© 2000 Federal-Mogul Corporation

© 2000 Federal-Mogul Corporation

Printed in U.S.A.

© 2000 Federal-Mogul Corporation Form No. I-3TEMP (Rev. 9/8/00)

Withstands high and low temperatures

Patented sealing bead design provides superior

Hole Lock design holds gasket in place during

Additional sealers are not generally required.

Printed in U.S.A.

Additional sealers are not generally required.

Hole Lock design holds gasket in place during installation.

sealability

Patented sealing bead design provides superior

Withstands high and low temperatures

Additional sealers are not generally required.

ATTACH AND ALIGN ASSEMBLY.

gasket sealer to both sides of gasket(s). It mating surface is pitted or corroded apply a

through the casting and the Hole Lock bolt hole

etlod gnitruom traeni NOITALLATZNI OT ROIRG

testing conditions. This new compound gasket of-

resulting from extensive engineering and extreme

guiued in this set is a new composite construction

The water outlet and/or water pump gasket(s) con-

LET AND WATER PUMP GASKETS

PLASTIC COMPOSITE WATER OUT-

**SAIT NOITALLATENI OR9-137** 

locations in the gasket.

fers the following featured.

Hole Lock design holds gasket in place during installation.

Patented sealing bead design provides superior sealability

Withstands high and low temperatures