




FEL-PRO INSTALLATION TIPS

CRANK CASE GASKET

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant, by applying a sealer to the mating surface.

Allow 1 to 2 minutes dry.



CREATE GASKET by applying a continuous 1/8" - 3/16" bead of anaerobic sealant down the center of the flange circling each hole.

REINSTALL CRANKCASE TO ENGINE. Torque securely to OEM specifications.

THIS WARNING MESSAGE IS SPECIFIC FOR ANAEROBIC FLANGE SEALANT

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumarate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-587 (Rev. 11/00)

Printed in U.S.A.




FEL-PRO INSTALLATION TIPS

CRANK CASE GASKET

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant, by applying a sealer to the mating surface.

Allow 1 to 2 minutes dry.



CREATE GASKET by applying a continuous 1/8" - 3/16" bead of anaerobic sealant down the center of the flange circling each hole.

REINSTALL CRANKCASE TO ENGINE. Torque securely to OEM specifications.

THIS WARNING MESSAGE IS SPECIFIC FOR ANAEROBIC FLANGE SEALANT

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumarate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-587 (Rev. 11/00)

Printed in U.S.A.




FEL-PRO INSTALLATION TIPS

CRANK CASE GASKET

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant, by applying a sealer to the mating surface.

Allow 1 to 2 minutes dry.



CREATE GASKET by applying a continuous 1/8" - 3/16" bead of anaerobic sealant down the center of the flange circling each hole.

REINSTALL CRANKCASE TO ENGINE. Torque securely to OEM specifications.

THIS WARNING MESSAGE IS SPECIFIC FOR ANAEROBIC FLANGE SEALANT

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumarate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-587 (Rev. 11/00)

Printed in U.S.A.




FEL-PRO INSTALLATION TIPS

CRANK CASE GASKET

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant, by applying a sealer to the mating surface.

Allow 1 to 2 minutes dry.



CREATE GASKET by applying a continuous 1/8" - 3/16" bead of anaerobic sealant down the center of the flange circling each hole.

REINSTALL CRANKCASE TO ENGINE. Torque securely to OEM specifications.

THIS WARNING MESSAGE IS SPECIFIC FOR ANAEROBIC FLANGE SEALANT

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumarate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-587 (Rev. 11/00)

Printed in U.S.A.