



FEL-PRO INSTALLATION TIPS

The OE manufacturer supplies five different Cyl. Head Gasket grades: A, B, C, Block Over-Bored, Block Over-Bored and Deck Milled. To identify each, the OE uses a "Hole" & "Slot" system as illustrated below.

Fel-Pro Engineers have designed two grades (.037" and .047" Thick) to function in place of the five offered by OE. The new Fel-Pro PermaTorqueMLS Cyl. Head Gasket part numbers are ink stamped to identify their coverage corresponding to OE.

OE Grade's:	A	B	C	Block Over-Bored	Block Over-Bored and Deck Milled
→					
Old Fel-Pro Part No's: →	26269PT (LH) 26270PT (RH) 26269PT1 (LH) 26270PT1 (RH)	26271PT (LH) 26272PT (RH) 26271PT1 (LH) 26272PT1 (RH)	26273PT (LH) 26274PT (RH) 26273PT1 (LH) 26274PT1 (RH)	N/A	N/A
New Fel-Pro PermaTorqueMLS Part No's: →	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26405PT (LH) 26406PT (RH) .047" Thick
Gasket Coverage (ink stamped on gasket): →	"STD THK COVERS GRADES A - B - C - OVERBORE"				"OVERBORE + .010"THK"
TORQUE SPECIFICATION:					
M12 BOLT -					
1st Step: 50 Nm (37 lb. ft.)					
2nd Step: 80 Nm (59 lb. ft.)					
3rd Step: 60 Degrees					
4th Step: 60 Degrees					
M8 Bolt -					
25 Nm (18 lb. ft.)					



FEL-PRO INSTALLATION TIPS

The OE manufacturer supplies five different Cyl. Head Gasket grades: A, B, C, Block Over-Bored, Block Over-Bored and Deck Milled. To identify each, the OE uses a "Hole" & "Slot" system as illustrated below.

Fel-Pro Engineers have designed two grades (.037" and .047" Thick) to function in place of the five offered by OE. The new Fel-Pro PermaTorqueMLS Cyl. Head Gasket part numbers are ink stamped to identify their coverage corresponding to OE.

OE Grade's:	A	B	C	Block Over-Bored	Block Over-Bored and Deck Milled
→					
Old Fel-Pro Part No's: →	26269PT (LH) 26270PT (RH) 26269PT1 (LH) 26270PT1 (RH)	26271PT (LH) 26272PT (RH) 26271PT1 (LH) 26272PT1 (RH)	26273PT (LH) 26274PT (RH) 26273PT1 (LH) 26274PT1 (RH)	N/A	N/A
New Fel-Pro PermaTorqueMLS Part No's: →	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26401PT (LH) 26402PT (RH) .037" Thick	↓ 26405PT (LH) 26406PT (RH) .047" Thick
Gasket Coverage (ink stamped on gasket): →	"STD THK COVERS GRADES A - B - C - OVERBORE"				"OVERBORE + .010"THK"
TORQUE SPECIFICATION:					
M12 BOLT -					
1st Step: 50 Nm (37 lb. ft.)					
2nd Step: 80 Nm (59 lb. ft.)					
3rd Step: 60 Degrees					
4th Step: 60 Degrees					
M8 Bolt -					
25 Nm (18 lb. ft.)					