Product information

Fully synthetic central hydraulic system oil that meet and exceed many OE specifications. Unique formulation allows for high thermal stability and excellent resistance to aging or break down. Maximum wear protection and proper friction behavior. Has outstanding low-temperature behavior and very high corrosion-protection. The fluid is a green color.

Properties

- excellent viscosity/temperature properties
- optimum stability to aging
- highest thermal stability
- excellent low temperature behavior
- outstanding corrosion protection

Specifications and approvals:


MAN M 3289

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW 81 22 9 407 758 • Fiat 9.55550-AG3 • Ford WSS-M2C 204-A • MB 345.0 • Opel 1940 766 • VW G 002 000 • VW G 004 000 • ZF TE-ML 02K

Technical data

Viscosity at 104 °F	19,6 mm²/s ASTM D 7042-04
Viscosity at 212°F	6,4 mm²/s ASTM D 7042-04
Viscosity index	322 DIN ISO 2909
Color / appearance	grün / green
Density at 59 °F	0,825 g/cm³ DIN 51757
Flash point	302 °F DIN ISO 2592
Pour point	-98 °F DIN ISO 3016
Foaming behavior at 75 °F	50/0 ml ISO 6247
Foaming behavior at 200 °F	35/0 ml ISO 6247



WARNING: Cancer and Reproductive Harmwww.P65Warnings.ca.gov

For power steering systems, hydropneumatic suspen-

sions, shock absorbers, etc. where a hydraulic fluid

meeting current product specification is required or

Available pack sizes

Areas of application

recommended.

Application

Comment

1 l Can plastic	20038 USA (-EN-)
1 l Can plastic	20326 CANADA (-EN-F-)
20 l Canister plastic	20407 USA AND CANADA (-EN- F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.



PI 34/15/09/2020