



INSTALLATION INSTRUCTIONS

Part Number: KT-2412

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® Filtercharger® seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

1. Remove the air box lid and push on the two tabs to remove the stock air filter. **Figs. 1 - 2**
2. Install the supplied plate onto the K&N filter. **Ensure that the filter pleats are oriented as shown in the image. Fig. 3**
3. Install the K&N filter into the air box by sliding the tabs on the plate into the slots and pushing down as shown. **Figs. 4 - 5**
4. Push the locking tabs outwards to engage the locks. Note they will not fit as tightly as the stock filter. **Fig. 6**
5. Re-install the air box lid to complete the installation.
6. Clean an area on the air box and apply the K&N Stop Decal. The decal will help notify others, who may be working on this vehicle, that this is a washable/re-usable air filter.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.