

FEL-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued

Form No. I-317 (Rev. 9/00) © 2000 Federal-Mogul Corp. Printed in U.S.A.

hold during operation. areas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

without break-in lubricant protection. INPORTANT: Do not install any seal

and shaft. Inpricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of **DNITATOR 3HT DNITAL LATING THE ROTACING**

FEL-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued -

Form No. I-317 (Rev. 9/00) © 2000 Federal-Mogul Corp. Printed in U.S.A.

hold during operation. steas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

without break-in lubricant protection. IMPORTANT: Do not install any seal

inpricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of PRIOR TO INSTALLATING THE ROTATING

FEL-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued -

Form No. I-317 (Rev. 9/00) Printed in U.S.A. © 2000 Federal-Mogul Corp.

pold during operation. areas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

> without break-in lubricant protection. INPORTANT: Do not install any seal

indricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of PRIOR TO INSTALLATING THE ROTATING

FFI-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued -

Form No. I-317 (Rev. 9/00) Printed in U.S.A. © 2000 Federal-Mogul Corp.

hold during operation. areas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

> without break-in lubricant protection. IMPORTANT: Do not install any seal

inbricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of **PRIOR TO INSTALLATING THE ROTATING**



FEL-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued

Form No. I-317 (Rev. 9/00) © 2000 Federal-Mogul Corp. Printed in U.S.A.

hold during operation. areas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

without break-in lubricant protection. INPORTANT: Do not install any seal

and shaft. Inpricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of **DNITATOR 3HT DNITAL LATING THE ROTACING**

FEL-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued -

Form No. I-317 (Rev. 9/00) © 2000 Federal-Mogul Corp. Printed in U.S.A.

hold during operation. steas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

without break-in lubricant protection. IMPORTANT: Do not install any seal

inpricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of PRIOR TO INSTALLATING THE ROTATING

FEL-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued -

Form No. I-317 (Rev. 9/00) Printed in U.S.A. © 2000 Federal-Mogul Corp.

pold during operation. areas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

> without break-in lubricant protection. INPORTANT: Do not install any seal

indricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of PRIOR TO INSTALLATING THE ROTATING

FFI-PRO INSTALLATION TIPS

Fel-Pro products are the result of exhaustive research and strict quality control. However, no sealing product is better than the quality of its installation.

ROTATING SHAFT SEALS

The Seal included in this set may vary in width from the seal being removed. The sealing lip of the replacement seal will position itself on a different area of the shaft in order to avoid seal leakage problems commonly associated with groove worn shafts.

- Continued -

Form No. I-317 (Rev. 9/00) Printed in U.S.A. © 2000 Federal-Mogul Corp.

hold during operation. areas thoroughly to determine that all seals TEST RUN ENGINE. Check all mating

> without break-in lubricant protection. IMPORTANT: Do not install any seal

inbricant, such as grease, on the sealing lip SHAFT AND/OR SEAL apply a thin coat of **PRIOR TO INSTALLATING THE ROTATING**