



FEL-PRO INSTALLATION TIPS

OIL PUMP

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant Cleaner/Primer to the mating surface.

Allow 1 to 2 minutes to dry.

SEAL OIL PUMP MATING SURFACE. Apply a thin continuous bead of anaerobic sealant to the oil pump.

Wipe off any excess sealant.

REINSTALL OIL PUMP. Torque securely to OEM specifications.

**THIS WARNING MESSAGE IS SPECIFIC FOR
22L PROLOCK FLANGE SEALANT.**

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumerate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-1968 (Rev. 8/00)

Printed in U.S.A.



FEL-PRO INSTALLATION TIPS

OIL PUMP

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant Cleaner/Primer to the mating surface.

Allow 1 to 2 minutes to dry.

SEAL OIL PUMP MATING SURFACE. Apply a thin continuous bead of anaerobic sealant to the oil pump.

Wipe off any excess sealant.

REINSTALL OIL PUMP. Torque securely to OEM specifications.

**THIS WARNING MESSAGE IS SPECIFIC FOR
22L PROLOCK FLANGE SEALANT.**

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumerate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-1968 (Rev. 8/00)

Printed in U.S.A.



FEL-PRO INSTALLATION TIPS

OIL PUMP

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant Cleaner/Primer to the mating surface.

Allow 1 to 2 minutes to dry.

SEAL OIL PUMP MATING SURFACE. Apply a thin continuous bead of anaerobic sealant to the oil pump.

Wipe off any excess sealant.

REINSTALL OIL PUMP. Torque securely to OEM specifications.

**THIS WARNING MESSAGE IS SPECIFIC FOR
22L PROLOCK FLANGE SEALANT.**

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumerate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-1968 (Rev. 8/00)

Printed in U.S.A.



FEL-PRO INSTALLATION TIPS

OIL PUMP

CLEAN MATING SURFACES.

PREPARE MATING SURFACES, for application of anaerobic sealant Cleaner/Primer to the mating surface.

Allow 1 to 2 minutes to dry.

SEAL OIL PUMP MATING SURFACE. Apply a thin continuous bead of anaerobic sealant to the oil pump.

Wipe off any excess sealant.

REINSTALL OIL PUMP. Torque securely to OEM specifications.

**THIS WARNING MESSAGE IS SPECIFIC FOR
22L PROLOCK FLANGE SEALANT.**

WARNING! EYE AND SKIN IRRITANT.

This product contains bisphenol-A fumerate resin and cumene hydroperoxide. Avoid contact with eyes and skin. In case of skin contact wash thoroughly with soap and water. For contact with eyes flush with water for 15 minutes and call a physician.

KEEP AWAY FROM CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer.

© 2000 Federal-Mogul Corporation
Form No. I-1968 (Rev. 8/00)

Printed in U.S.A.